

For more information and a complete guide to our product offering, visit us on the web at [rotarylif.com](http://rotarylif.com) or contact your local distributor today.



**Rotary World Headquarters**  
2700 Lanier Drive  
Madison, IN 47250, USA  
[www.rotarylif.com](http://www.rotarylif.com)

**North America Contact Information**

Sales: p 800.640.5438  
f 800.578.5438  
e [userlink@rotarylif.com](mailto:userlink@rotarylif.com)  
Tech. Support: p 800.445.5438  
e [techlink@rotarylif.com](mailto:techlink@rotarylif.com)

**World Wide Contact Information**

World Headquarters/USA: 1.812.273.1622  
Canada: 1.905.812.9920  
European Headquarters/Germany: +49.771.9233.0  
United Kingdom: +44.178.747.7711  
Australasia: +60.3.5192.5910  
Latin America/Caribbean: 1.812.273.1622  
Middle East/Northern Africa: +49.771.9233.0  
Southern Africa: 1.812.273.1622  
Brazil: +55.11.4534.1995



[www.rotarylif.com](http://www.rotarylif.com)

**Rotary World Headquarters**  
2700 Lanier Drive  
Madison, IN 47250, USA

**Contact Information**

Sales: p 800.640.5438  
f 800.578.5438  
e [userlink@rotarylif.com](mailto:userlink@rotarylif.com)  
Tech. Support: p 800.445.5438  
f 800.822.6502  
e [userlink@rotarylif.com](mailto:userlink@rotarylif.com)

**FIND US ON**



Lit# Rotary\_LD\_HD\_2Post\_Overview\_2014.03  
©2014 VEHICLE SERVICE GROUP<sup>SM</sup>. Printed in U.S.A., All Rights Reserved. Unless otherwise indicated, ROTARY LIFT, VEHICLE SERVICE GROUP<sup>SM</sup>, DOVER and all other trademarks are property of Dover Corporation and its affiliates.



# Two Post

LIGHT DUTY / HEAVY DUTY LIFTS



# ROTARY LIFT

THE WORLD'S MOST TRUSTED LIFT

Model Shown: SPOA10X 10,000 lbs. capacity SHOCKWAVE equipped 2 post lift



[www.rotarylif.com](http://www.rotarylif.com)



# 7,000 - 10,000 lb. Capacity 2 Post Asymmetric Lifts

Lifts shown with optional accessories



Model shown:  
SPOA10U5G5RD

↑ **25 second  
rise time!**  
↓ **19 second  
descent!**

Speeds based on weight of vehicle

## Rotary Lift **SHOCKWAVE**<sup>TM</sup> TWICE As Fast As Any Standard Lift!



**2X FASTER RISE  
AND DESCENT**



**LASER-BEAM GUIDED  
VEHICLE CENTERING**



**MORE PRODUCTIVITY—  
HAPPIER TECHNICIANS.**



***"We can get them (vehicles) up in the air and spend more time on their inspection which is the most important portion of our service. It's amazing how much faster we can service vehicles."***

*Brent Ross, Service Director, Germain Nissan*

### Asymmetric Lift Arm Adapter Packages



**Three-Stage Flip-Up  
Adapters with built-in  
height adapters on  
standard arms**



Model shown: SPOA10N700BL  
with standard arms and three-stage flip-up adapters



**RA - 3 stage arms give more reach  
- perfect for *low profile* vehicles**



Model shown: SPOA10N5G0BL  
with three-stage front arms and round rubber adapters



### 7,000 - 10,000 lb. SHOCKWAVE Asymmetric Two Post Lifts

Two-Post Lifts*	SHOCKWAVE EQUIPPED					10K lb. Asymmetric Two Post Lifts		
	SPOA10U705BL SPOA10U705RD Standard Arms Flip Up Adapters	SPOA10U5T5BL SPOA10U5T5RD Three-Stage Arms Truck Adapters	SPOA10U5G5BL SPOA10U5G5RD Three-Stage Arms Round Adapters	SPOA7U7N5BL SPOA7U7N5RD Fixed Front Pads with 3-Stage Rear Arms	SPOA7U6X5BL SPOA7U6X5RD Drive-Over Moveable Pads	SPOA10N700BL SPOA10N700RD Standard Arms Flip Up Adapters	SPOA10N5T0BL SPOA10N5T0RD Three-Stage Arms Truck Adapters (TA)	• SPOA10N5G0BL • SPOA10N5G0RD Three-Stage Arms Round Adapters (RA)
Capacity	10,000 lbs.	10,000 lbs.	10,000 lbs.	7,000 lbs.	7,000 lbs.	10,000 lbs.	10,000 lbs.	10,000 lbs.
Rise**	75-3/4" - 81-1/4"	74-9/16" - 85-1/16"	74-1/2" - 76-3/4"	76-7/8"	77"	72-3/4" - 78-1/4"	71-9/16" - 82-1/16"	71-1/2" - 73-3/4"
Overall Height	12' - 4-1/2"					11' - 8-1/2"		
Overall Width	11' - 5-1/2"					11' - 5-1/2"		
Drive-thru	95 - 1/4"		95 - 1/4"	83 - 3/8"	79"	95 - 1/4"		
Inside Columns	107 1/4"					107 1/4"		
Front Arm Min/Max	20-1/2" - 40-3/4"	21-5/8" - 43-1/2"	21-5/8" - 43-1/2"	N/A	N/A	20-1/2" - 40-3/4"	21-5/8" - 43-1/2"	21-5/8" - 43-1/2"
Rear Arm Min/Max	40-1/4" - 61"	34-1/2" - 58"	34-1/2" - 58"	64-1/2" - 30-3/8"	N/A	40-1/4" - 61"	34-1/2" - 58"	34-1/2" - 58"
Min Adapter Height	4 - 3/4"		3 - 1/2"	Rear arm: 3-3/4" Front pad: 2-7/8" Front arm: 5-1/4"	2 - 5/8"	4-3/4"		3-1/2"
Min Bay Size	12' x 24'		12' x 24'	12' x 24'	12' x 24'	12' x 24'		
Ceiling Height Min	12' - 4 3/4"					12'		
Motor / Voltage 1Ø	5 HP / 110 v		5 HP / 110 v	5 HP / 110 v	5 HP / 110 v	2 HP, 208-230V		
Time of Full Rise	25 seconds		25 seconds	25 seconds	25 seconds	45 seconds		
Time of Descent	19 seconds		19 seconds	19 seconds	19 seconds	40 seconds		

• 3-stage arms 13 Locking Positions \* BL = Blue/ RD = Red \*\*Rise measures lowest or highest position of the supplied adapters from floor to full cylinder stroke






# 10,000 - 18,000 lb. Capacity 2 Post Symmetric Lifts

Lifts shown with optional accessories

Available with SHOCKWAVE™



10,000 lbs.  
Capacity



Model shown:  
SPO10N700BL

SPO10SW  
Minimum  
Required  
Ceiling  
Height: 12' 4-3/4"



## Arm Adapters Packages

**10,000 lb. capacity lift:**

**Three-Stage Flip-Up Adapters** with  
built-in height adapters on standard arms

**12 to 18,000 lb. capacity lift:**

**Thread Up Stackable Inserts** designed for heavier  
vehicles, (additional stack adapters available)



- TA and RA Adapters also available for  
10,000 lb. capacity lift
- TA lift models include stackable inserts



15,000 lbs.  
Capacity



Low Ceiling  
Model  
Available!



Model shown:  
SPO15N310BL

Available with SHOCKWAVE™



12,000 lbs.  
Capacity

3 Stage Arms  
for Added Reach!

Low Ceiling  
Available!



Model shown:  
SPO12N7T0BL

## 10,000 - 18,000 lb. Two Post Symmetric Lifts

Two-Post Lifts\*

- 3-stage front arms
- \* BL= Blue / RD=Red

AVAILABLE WITH  
SHOCKWAVE

	SPO10N700BL SPO10N700RD Standard Arms Flip Up Adapters	• SPO10N5T0BL • SPO10N5T0RD Three-Stage Arms Truck Adapters (TA)	• SPO10NG50BL • SPO10NG50RD Three-Stage Arms Round Adapters (RA)	• SPO12N7T0BL • SPO12N7T0RD Three-Stage Arms Truck Adapters (TA)	SPO15N310BL SPO15N310RD Standard Arms Truck Adapters (TA)	SPO15LC310BL SPO15LC310RD Standard Arms Truck Adapters (TA)	SPO18N310BL SPO18N310RD Standard Arms Truck Adapters (TA)	SPO18LC310BL SPO18LC310RD Standard Arms Truck Adapters (TA)
Capacity	10,000 lbs.	10,000 lbs.	10,000 lbs.	12,000 lbs.	15,000 lbs.		18,000 lbs.	
Rise**	72-5/8"-78-1/8"	72-5/8"-75-1/8"	72-1/2"-74-3/4"	72-3/4"-80-1/4"	76-7/8"-88-7/8"		76-7/8"-88-7/8"	
WITH SHOCKWAVE	75-5/8"-81-1/8"	75-5/8"-78-5/8"	75-1/2"-77-3/4"	75-3/4"-83-1/4"				
Overall Height		11' 8-1/2"	12' 4-1/2"	13'-8"	15'-16'-6"	13'-6"-14'-6"	15'-16'-6"	13'-6"-14'-6"
Required Ceiling Height		12'	12' 4-3/4"	14'	15'-1"	13'-7"	15'-1"	13'-7"
Overall Width	11'-5-1/2"	11'-5-1/2"	11'-5-1/2"	11'-5-5/8"	12'-11"		12'-11"	
Drive-thru Width	8'-6-1/2"	8'-6-1/2"	8'-6-1/2"	8'-6-3/8"	8'-9-3/4"		8'-9-3/4"	
Inside Columns		114 1/2"		113 3/8"	120"			
Front Arm Min/Max	31"-54"	27-1/2"-59"	27-1/2"-59"	27-1/2"-59"	37-1/2"-62"		37-1/2"-62"	
Rear Arm Min/Max	31"-54"	27-1/2"-59"	27-1/2"-59"	27-1/2"-59"	37-1/2"-62"		37-1/2"-62"	
Min Adapter Height	4-3/4"	4-3/4"	3-5/8"	4-3/4"	5-3/4"		5-3/4"	
Motor/Voltage	2 HP, 208-230V	2 HP, 208-230V	2 HP, 208-230V	2 HP, 208-230V, 1Ø	2 HP, 208-230V, 1Ø		2 HP, 208-230V, 1Ø	
WITH SHOCKWAVE	5HP/110v	5HP/110v	5HP/110v	5HP/110v				
Time of Full Rise / Descent		45 secs. / 40 secs.		60 secs. / 40 secs.	Time of Full Rise: 85 secs.		Time of Full Rise: 85 secs.	
WITH SHOCKWAVE		25 secs. / 19 secs.		30 secs. / 20 secs.				
Min Bay Size	12' x 24'	12' x 24'	12' x 24'	12' x 26'	15' x 30'		15' x 30'	

\*Rise measures lowest or highest position of the supplied adapters from floor to full cylinder stroke

## 2 Post Lift Accessories

The accessories listed below are commonly used with two-post lifts to increase productivity in the bay.

	Rotary											
Lifts & Accessories	Extended Height GM Adapters	Extended Height Truck Adapters	1/2" Pad Adapter	1" Pad Adapter	2-1/2" Pad Adapter	Thread-Up Frame Engaging Adapter	Round Rubber Adapter for Unibody Vehicles	Stackable Extensions	Air/Electric Utility Box	Tool Holder	Door Defender	
SPOA10	FJ6133BK	FJ6115BK	FJ6138BK	FJ6190YL	FJ6139BK				FA5911BK	FA5191	N823	
SPO10	FJ6133BK	FJ6115BK	FJ6138BK	FJ6190YL	FJ6139BK				FA5911BK	FA5191	N823	
SPOA10-RA						FJ6197	Included	FJ7880BK	FA5911BK	FA5191	N823	
SPOA10-TA						Included	FJ6225	Included	FA5911BK	FA5191	N823	
SPO10-TA						Included	FJ6225	Included	FA5911BK	FA5191	N823	
SPO10-RA						FJ6197	Included	FJ7880BK	FA5911BK	FA5191	N823	
SPO12-TA						Included	FJ6225	Included	FA5911BK	FA5191	N823	
SPO15/SPO15-LC								Included	FA5911BK	FA5191	N823	
SPO18/SPO18-LC								Included	FA5911BK	FA5191	N823	

## Make sure your lifts are Gold Certified!

It takes a combination of the right design, engineering excellence and quality manufacturing to earn this certification. It is extra assurance for you that your lift meets the highest industry safety and performance standards. **Look for the Gold Label!** Check out a complete listing of certified lifts at [www.autolift.org](http://www.autolift.org).

