

# 2600 / 2800

## WHEEL BALANCERS



# HOFMANN



# 2600 / 2800

**Premium wheel balancers designed  
for speed, accuracy and dependability.**

## WHEEL BALANCER

- **Unsurpassed accuracy**

New balancing technology uses 512 precise weight positions. Special "User-calibration" alerts operator when readjustment is needed. Operator then can calibrate and readjust the balancer in two easy steps, guaranteeing accuracy.

- **Longer mounting shaft**

40mm balancer shaft is 30% larger than most competitive brands. Allows mounting of widest wheels using standard accessories. "ZipLock" quick nut provides fastest wheel mounting/demounting system in the industry.

- **Twelve balancing modes**

The 2600/2800 are equipped with twelve different balancing modes, five alloy modes, two hidden weight, R.V. mode for medium/heavy duty tires, Internal Pre-Balance mode for over-sized off-road tires, "Pro-Match" tire/wheel matching, dynamic, and static to handle all wheel applications.

- **"HSP"/ "OSP" Weight Placement**

Patented **H**idden **S**poke **P**lacement allows the operator to hide correction weights behind the spokes on rims that have no outer flange. Patented **O**perator **S**electable **P**ositioning allows the operator to select the correction location by rim design.

- **Automatic data / weight location / shaft lock**

The 2600 precisely enters the rim diameter /distance automatically, the 2800 is equipped with all automatic data entry, diameter/distance/ width. Both balancers feature automatic wheel positioning, the tire is rotated to the imbalance location then the pedal operated shaft lock holds the wheel for attachment of the the weights.

### Specifications

Shipping weight.....	400
Rim width range.....	1.0" - 20"
Rim diameter range.....	8.0" - 24"
Max. tire diameter.....	44"
Max. wheel weight.....	150 lbs.
Electric requirement.....	115V 50/60hz 1 ph or 230V50/60hz 1 ph
Motor.....	1.0 Hp
Cycle time.....	From 6 seconds
Read-outs.....	Gram or Ounce
Accuracy.....	1 g or 0.05 oz
Balancing Modes.....	12

### Standard Accessories

Automotive Cone Kit.....	1 5/8" - 4 1/2"
"ZipLock" quick-nut, pressure cup with rubber scratch proof cap, rim width gauge, calibration tool, storage pegs.	

**Hofmann manufactures a complete line of wheel service equipment**



**HOFMANN**  
USA



P.O. Box 178157 Nashville, TN 37217  
(800) 251-4500 • (615) 331-7851  
FAX (615) 331-8176  
Internet: <http://www.hofmann-usa.com>

**We reserve the right to make engineering changes without notice.**  
© Copyright 2002, Hofmann

**HOFMANN**  
Canada



P.O. Box 1270, Belleville, Ontario K8N 5E9  
(613) 962-9138 FAX (613) 962-8302  
Internet: <http://www.hofmann.ca>  
E-mail: [hofmann.ca@sympatico.ca](mailto:hofmann.ca@sympatico.ca)

**Form # 2628-0902**