



- Large graphical screen
- Scroll bar capability
- Hot keys

*Easy-to-use controls, compact size, and an integrated printer make the EXP-800 the ideal choice for service shops looking to increase customer satisfaction and battery revenue by making preventative maintenance a part of their value-added solutions.*

### SPECIFICATIONS:

#### Model:

##### • EXP-800

EXP-800 Battery and Electrical System Diagnostic Analyzer with integrated printer, lead stud adapter set, 4-ft. cable set, and carrying bag

##### • EXP-800L

Everything included with the EXP-800, except with a 10-ft. cable set

#### Applications:

- 6- and 12-volt batteries
- 12- and 24-volt charging systems

#### Power Requirements:

- (6) AA Alkaline batteries

#### Battery Applications:

- Automotive
- Marine battery
- Motorcycle
- Lawn and Garden

#### Battery Chemistries:

- Regular (flooded)
- AGM Spiral
- AGM
- Gel

#### Rating System Range

CCA	100 – 3000
CA	100 – 3000
MCA	100 – 3000
JIS	By JIS number
DIN	100 – 1000
SAE	100 – 3000
IEC	100 – 1000
EN	100 – 3000

#### DC Voltage

0 - 60 V, 0.05% +/- .03 VDC

#### Measured Temperature

-20 to 200° F 1.0% +/- 5°  
(-28.8 to 93.3° C)

#### Display:

- 128 x 64 pixel graphic, backlit display

#### Operating Temperature:

- 32° F – 120° F (0° C – 49° C)

#### Housing Material:

- ABS plastic

#### Dimensions:

- 9 1/2 in H x 4 in W x 2 1/2 in D

#### Weight:

- 1 lb / 427 g

#### Languages:

- English
- Spanish
- French-Canadian

Use your smartphone QRC scanner app to view these EXP-800 videos:



Features and benefits



Preparing for a battery test



Testing a battery




EXP-800

## EXP800

WILLS CAR CATTLE  
1060 W. ADDISON S  
CHICAGO, IL  
60610  
800 867-5309  
WWW.CATTLE.COM

10/19/2012  
2:32 PM



NO START TEMP: 10°F

BATTERY MAY NOT START  
VEHICLE AT OR BELOW  
THIS TEMPERATURE OR  
IN EXTREME CONDITIONS

BATTERY AGE: 81 MO.  
AVERAGE BATTERY LIFE  
IN THIS AREA 59 MO

BATTERY IS  
APPROACHING THE END  
OF ITS USEFUL LIFE.

SUGGEST REPLACEMENT

Sample Printout

#### Corporate Headquarters

Willowbrook, IL USA  
Phone: 1.630.323.2800  
Toll Free in US: 1.800.776.1995  
Toll-Free in Canada: 1.866.592-8053

#### European Sales

Midtronics b.v.  
European Headquarters  
Houten, The Netherlands  
Serving Europe, Africa, the Middle East,  
and The Netherlands  
Phone: +31 306 868 150

#### Midtronics China Office

China Operations  
Shenzhen, China  
Phone: +86 755 8202 2036

#### Asia/Pacific (excluding China)

Contact Corporate Headquarters  
Phone: +1.630.323.2800

#### Midtronics India

Mumbai, India  
Phone: +91.989 237 6661