

A2024 Series Tire Changers

The market choice for reliability and long-lasting performance is designed for low-profile/ultra-high performance tires. Run-flat certified by all major tire manufacturers. PAX capable with accessory kit.

A2024TI-DV



Features

- Built-in table inflator with jets in the jaws
- Unique mount/demount head does not touch the rim during operation
- Locking handle locks head away from the rim
- Powerful action bead-breaker blade follows bead to inside rim contour
- Heavy-duty turntable rotates in either direction
- Rebuildable stainless steel cylinders
- Heavy-duty stainless steel turntable
- Safe, fast, profitable and affordable
- Pneumatic-locking mount/demount head
- Sturdy tilt-back tower
- Tire pressure sensor style rims changes safely
- Interchangeable locking peaks on jaws
- Table top rotation double-speed RPM 6-18
- Shipping weight 560 lbs.

A2024TI-DV-20



Same features as the A2024TI

PLUS SP2000 SUPER POWER UNIT

- Pneumatic-powered upper disc holds bead into the wheel drop for mounting
- Designed for low-profile, EMT and high-performance tires and wheels
- Loosening upper bead for demounting
- Push down upper bead for lubrication and tire tool insertion
- Lowering upper bead for inspection between bead and demount head
- Lowering upper bead for inserting the bead clamp; this clamp makes it possible to lift the bead over the mount/demount head
- Pneumatic-powered lower lifting arm holds lower bead into the wheel drop while lower bead is lifted over the mount/demount head
- Pneumatic-powered lower lifting arm loosens lower bead if it reseats
- Tire pressure sensor style rims changes safely
- Shipping weight 750 lbs.

A2024TI-DV-2015



Same features as the A2024TI-20

PLUS PU1500 POWER ASSIST UNIT

- Pneumatic powered
- Wheel and bead pressing arm
- Bead lifter
- Maintains bead in drop center
- Eliminates bead stress
- Eliminates wheel damage
- One person operation to change even the most difficult tires
- PAX capable with PAX kit
- Rim clamping assist
- Tire pressure sensor style rims changes safely
- Shipping weight 900 lbs.

Specifications

- | | |
|-----------------------------|------------|
| • Ext. Rim Size | 10"-24" |
| • Optional w/Adapter | 10"-26" |
| • Int. Rim Size | 13"-26" |
| • Voltage | 110V 1 Ph |
| • Rim Width | 3,5"-14" |
| • Max. Tire Diameter | 43" |
| • Air Pressure | 150 psi |
| • Bead Breaker Power @ Shoe | 3500 lbs |
| • Torque | 737 ft/lbs |

Standard Accessories

- Lube Bucket
- Lube Brush
- Tire Lever
- M/D Head Bottom Inserts
- Set of Jaw Protectors
- B/B Blade Protector
- Bead Clip
- Set of Inserts
- Tire Lever Cover