

HIGH VOLUME, SHORT BALANCING CYCLE. UNCOMPROMISED ACCURACY

Featuring fast data enty and easyWeight.

NTRODUCING THE **B400L** VIDEO WHEEL BALANCING SYSTEM

JohnBean

HEB400L VIDEO WHEEL BALANCER. PATENTED VIRTUAL PLANE TECHNOLOGY.

PATENTED INNOVATION FOR FAST, ACCURATE RESULTS

Unparalleled speed and accuracy, with non-contact rim width acquisition via smartSonar, exact weight placement via the easyWeight pinpoint laser, and a 19" monitor featuring step-by-step video instructions and an intuitive user interface.

KEY FEATURES

easyWeight

 A laser pointer allows fast, accurate and easy positioning of adhesive weights on the wheel

ACCURATE AND OUICK CLAMPING

 With the included cones or the optional stud-hole flange accessory, clamping with the included Quick Nut is fast and easy

DATA ENTRY

 The B400L is equipped with semi-automatic data entry for rim diameter and offset

SHORT BALANCING CYCLE

Extremely short balancing cycle of 4.5 seconds

INCLUDED FOUR CONE KIT

Small: 1.6" - 3"
Medium: 2.8" - 3.9"
Large: 3.8" - 4"
Truck: 3.4" - 5.4"

INTUITIVE USER INTERFACE PROTECTIVE WHEEL GUARD OUICK NUT FOR ACCURATE AND QUICK CLAMPING MAIN SHAFT LOCK

EQUIPMENT SPECIFICATIONS

- Part Number: EEWB562AL
- Rim Diameter Manual Entry: 8" 32" (20 81.3 cm)
- Rim Diameter Semi-automatic Entry: 8" 25" (20 63 cm)
- Rim Width Smart Sonar: 3" 15" (8 38 cm)
- Shaft Diameter: 40mm
- Shaft Length: 8.86" (22.5cm)
- Measuring Speed: 200 RPM

- Balancing Accuracy: 1g / 0.035oz
- Wheel Diameter Range: 8" 42" (20.32cm 106.68cm)
- Dimensions (D x W x H): 52" x 35" x 73" (132.1 x 89 x 185.4cm
- Shipping Weight: 352 lbs (160kg)
- Power Requirements: 115V 1Ph 50/60Hz 8A

For more information regarding the **B400L** call **800.362.4618 (US)** or **800.362.4608 (Canada)** www.johnbean.com / www.johnbean.ca

John Bean is committed to product innovation and improvement. Therefore, specifications listed in this sell sheet may change without notice. ©2016 Snap-on Incorporated. All rights reserved. John Bean is a trademark, registered in the United States and other countries, of Snap-on Incorporated. All other marks are marks of their respective holders. 02/16 SS143390D

